



## VisiCom Specifications

---

### POWER

- Peak Power Consumption .....2 watts
- Typical Idle Power Consumption .....Less than 1 watt
- Nominal Operating Voltage ..... 115 VAC, 50/60 Hertz  
220 VAC, 50/60 Hertz also available
- Power Supply .....Miniature plug-in wall cube

### FUNCTIONAL


- Signalling Frequency .....2.4 GHz
- Clock Speed .....3.58 MHz
- Reset on Power Up.....Automatic
- Primary Communications.....Zigbee RF
- Optional Communications.....Direct Wire
- RJ-11 Port for RF/Direct Wiring .....RS-485 network characteristics

### ENVIRONMENTAL

- Operating Temperature Range.....0° – 32° C (50° – 122° F)
- Humidity Range .....0 – 90%, non-condensing
- Top Surface .....Customizable clear overlay, subsurface printed

### PHYSICAL

- Dimensions.....Front to back – 4.0 inches (10.16 cm)  
Left to right – 5.0 inches (12.70 cm)  
Maximum Height – 2.75 inches (6.98 cm)
- Weight .....1.2 pounds (544 g)
- Protrudes From Wall .....2.95 inches (7.49 cm)  
(when mounted using optional wall bracket)



### OPERATIONAL

- Capacity – Personnel.....Models for calling 8, 16 or 100 staff members
- Call-from Locations.....Standard and Extended Models – 26, maximum  
Pro Model – 52, maximum
- Other Messages .....Ph (Phone Call), Pt (Patient), Fd (Front Desk)
- Active Messages.....16, automatic sequencing display
- Chime volume.....On/off with fully adjustable sound level
- Chime tone .....Seven distinctive, programmable chime tones